74

#### **RTJ400 OPERATION**

# CHAPTER 16 Quick Reference

**Board Width Selection for Dovetails** 

## Through Dovetails (Full Pitch)

Board widths are based on the number of full tails (A) in your design. Board edges should always end in a half-pin (B).



		Board	Widt	h Sele	ction	for Th	rough	Dove	tails		
No. of Tails		1	2	3	4	5	6	7	8	9	10
s	Min	1 7⁄16"	3"	4 %16"	6 1⁄8"	7 11⁄16"	9 1⁄4"	10 <sup>13</sup> ⁄16"	12 3⁄8"	13 <sup>15</sup> ⁄16"	15 1⁄2"
Inches	Exact	1 %16"	3 1⁄8"	4 11/16"	6¼"	7 <sup>1</sup> 3⁄16"	9 <del>3</del> ⁄8"	10 15/16"	12 ½"	14 1⁄16"	15 5⁄8"
-	Max	1 15/16"	3 1⁄2"	5 1⁄16"	6 5⁄8"	8 <sup>3</sup> ⁄16"	9 ¾"	11 5⁄16"	12 7⁄8"	147/16"	16"
No. of Tails		1	2	3	4	5	6	7	8	9	10
ters	Min	37	76	116	156	196	235	275	315	355	394
Millimeters	Exact	40	80	119	159	199	239	278	318	358	398
W	Max	49	89	129	169	208	248	288	328	367	407

#### **Half-Pitch Through Dovetails**

Board widths are based on the number of full tails (A) in your design. Board edges should always end in a half-pin (B).



				l	Boai	rd Wi	idth	Selec	tion	for	Half	Pitch	Thre	bugh	Dove	etails					
No. of Tails		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
s	Min	<sup>2</sup> 3/ <sub>32</sub> "	1 1⁄2"	2 %32"	3 1⁄16"	3 27/32"	4 5⁄8"	5 <sup>1</sup> 3⁄32"	6 3⁄16"	6 <sup>31</sup> /32"	7 3⁄4"	8 <sup>17</sup> / <sub>32</sub> "	9 5⁄16"	10 3⁄32"	10 7⁄8"	11 <sup>21</sup> / <sub>32</sub> "	12 7/16"	13 7⁄32"	14"	14 25/32"	15 %16"
Inches	Exact	<sup>25</sup> / <sub>32</sub> "	1 %16"	2 11/32"	3 1⁄8"	3 <sup>29</sup> ⁄32"	4 11⁄16"	5 <sup>15</sup> / <sub>32</sub> "	6 ¼"	7 ¼32"	7 <sup>13</sup> ⁄16"	8 <sup>19</sup> / <sub>32</sub> "	9 3⁄8"	10 5⁄32"	10 15/16"	11 <sup>2</sup> 3/ <sub>32</sub> "	12½"	13 %32"	14 1⁄16"	14 27/32"	15 5⁄8"
-	Max	<sup>29</sup> / <sub>32</sub> "	1 11/16"	2 15/32"	3 ¼"	4 1/32"	4 <sup>13</sup> ⁄16"	5 <sup>19</sup> ⁄32"	6 3⁄8"	7 5⁄32"	7 <sup>15</sup> ⁄16"	8 <sup>2</sup> 3⁄32"	9 1⁄2"	10 %32"	11 1⁄16"	11 27/32"	12 5⁄8"	13 13/32"	14 ¾16"	14 <sup>31</sup> / <sub>32</sub> "	15 ¾"
No. of Tails		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
ters (	Min	18	38	58	77	97	117	137	156	176	196	216	235	255	275	295	314	334	354	374	393
Millimet	Exact	20	40	59	79	99	119	138	158	178	198	217	237	257	277	296	316	336	356	375	395
M	Max	23	43	62	82	102	122	141	161	181	201	220	240	260	280	299	319	339	359	378	398

#### **Half-Blind Dovetails**

Board widths are based on the number of full tails (A) in the joint design. Board edges always end with a half pin (B). Board widths in the chart below may be increased by 1/4" [6mm] or decreased by 1/8" [3mm] if required.



						Boar	d Wi	dth S	Selee	ction	for	Half-I	Blinc	l Dov	etails	5					
No. of Tails		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Ś	Min	<sup>21</sup> / <sub>32</sub> "	1 1⁄16"	2 7/32"	3 "	3 <sup>25</sup> / <sub>32</sub> "	4 %16"	5 11/32"	6 1⁄8"	6 <sup>29</sup> / <sub>32</sub> "	7 11⁄16"	8 15/32"	9 ¼"	10 1/32"	10 <sup>13</sup> ⁄16"	11 <sup>19</sup> ⁄32"	123⁄8"	13 5⁄32"	13 15/16"	14 23/32"	15 ½"
Inches	Exact	<sup>25</sup> / <sub>32</sub> "	1 %16"	2 11/32"	3 1⁄8"	3 <sup>29</sup> ⁄32"	4 <sup>1</sup> 1⁄16"	5 <sup>15</sup> / <sub>32</sub> "	6¼"	7 ¼32"	7 <sup>13</sup> ⁄16"	8 <sup>19</sup> / <sub>32</sub> "	9 3⁄8"	10 5⁄32"	10 <sup>15</sup> ⁄16"	11 <sup>2</sup> 3/ <sub>32</sub> "	12½"	13 %32"	14 1⁄16"	14 27/32"	15 5⁄8"
-	Max	1 1⁄32"	1 <sup>13</sup> ⁄16"	2 1%32"	3 3⁄8"	4 5/32"	4 <sup>15</sup> ⁄16"	5 <sup>23</sup> / <sub>32</sub> "	6 ½"	7 %32"	8 ¼16"	8 <sup>27</sup> / <sub>32</sub> "	9 5⁄8"	10 <sup>1</sup> 3⁄32"	11 ¾16"	11 <sup>31</sup> / <sub>32</sub> "	12¾"	13 17/32"	14 5⁄16"	15 3⁄32"	15 7⁄8"
No. of Tails		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
ters	Min	17	37	56	76	96	116	136	155	175	195	215	234	254	274	294	313	333	353	373	392
Millimeters	Exact	20	40	60	79	99	119	139	158	178	198	217	237	257	277	297	316	336	356	376	395
Mil	Max	26	45	65	85	105	124	144	164	184	203	223	243	263	282	302	322	342	361	381	401

#### **Board Width Selection for Box Joints**

#### 3/8" Box Joints

Board widths are determined by the total number of pins and sockets in the joint design and whether the joint is symmetrical or asymmetrical. Use this chart to determine board widths up to 16" [406mm].

ı at
f piı
•

Asymmetrical joints have a full pin on one edge and a full socket on the other edge. The total number of pins and sockets is always an even number.

				S	ymm	etric	al Boa	ard V	Vidth	Cha	rt for	3/8"	Box J	oints						
Total Pins & Sockets	3	5	7	9	11	13	15	17	19	21	23	25	27	29	31	33	35	37	39	41
Inches	1 5⁄32"	1 15/16"	2 <sup>23</sup> / <sub>32</sub> "	3 1⁄2"	4 %2"	5 ¼16"	5 <sup>27</sup> /32"	6 5⁄8"	7 <sup>1</sup> 3⁄32"	8 ¾16"	8 <sup>31</sup> /32"	9 ¾"	10 17/32"	11 5⁄16"	12 3⁄32"	12 7⁄8"	13 21/32"	14 7/16"	15 7⁄32"	16
Millimeters	29	49	69	89	109	129	148	168	188	208	228	248	267	287	307	327	347	367	387	406
				1	Asym	metri	ical Bo	bard	Widt	n Cha	rt for	3/8"	Box J	oints						
Total Pins & Sockets		4	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40
Inches		1 %16"	2 11/32"	3 1/8"	3 <sup>29</sup> /32"	4 11/16"	5 <sup>15</sup> / <sub>32</sub> "	6¼"	7 ¼32"	7 13/16	8 19/32"	9 3⁄8"	10 5⁄32"	10 15/16"	11 23/32"	12 ½"	13 %32"	14 1⁄16"	14 27/32"	15 5⁄8"
Millimeters		40	60	79	99	119	139	159	179	198	218	238	258	279	298	318	337	357	377	397

### 3/8" Half-Blind Box Joints

Board widths are based on the number of full tails (A) in the joint design. Board edges always end with a half pin (B). Board widths may be increased by 1/4" [6mm] or decreased by 1/8" [3mm] if required.

number of pins



					Во	ard V	Vidtl	n Sele	ectio	on fo	r 3/8	" Hal	f-Bli	nd Bo	ox Joi	nts					
No. of Tails		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
s	Min	<sup>21</sup> / <sub>32</sub> "	1 1⁄16"	2 7/32"	3 "	3 <sup>25</sup> / <sub>32</sub> "	4 %16"	5 11/32"	6 1⁄8"	6 <sup>29</sup> /32"	7 11⁄16"	8 15/32"	9¼"	10 1/32"	10 13/16"	11 <sup>19</sup> ⁄32"	12 3⁄8"	13 5⁄32"	13 15/16"	14 23/32"	15 ½"
Inches	Exact	25/32"	1 %16"	2 11/32"	3 1⁄8"	3 <sup>29</sup> ⁄32"	4 11⁄16"	5 <sup>15</sup> /32"	6¼"	7 ¼32"	7 <sup>13</sup> ⁄16"	8 <sup>19</sup> / <sub>32</sub> "	9 <del>3/</del> 8"	10 5⁄32"	10 15/16"	11 <sup>23</sup> / <sub>32</sub> "	12 1⁄2"	13 %32"	14 ¼16"	14 27/32"	15 5⁄8"
_	Max	1 1⁄32"	1 <sup>13</sup> ⁄16"	2 <sup>1</sup> %2"	3 3⁄8"	4 5⁄32"	4 <sup>15</sup> ⁄16"	5 <sup>23</sup> / <sub>32</sub> "	6½"	7 %32"	8 ¼16"	8 <sup>27</sup> / <sub>32</sub> "	9 5⁄8"	10 13/32"	11 ¾16"	11 <sup>31</sup> / <sub>32</sub> "	12 3⁄4"	13 17/32"	14 5⁄16"	15 ¾32"	15 7⁄8"
No. of Tails		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
ters	Min	17	37	56	76	96	116	136	155	175	195	215	234	254	274	294	313	333	353	373	392
Millimet	Exact	20	40	60	79	99	119	139	158	178	198	217	237	257	277	297	316	336	356	376	395
Mil	Max	26	45	65	85	105	124	144	164	184	203	223	243	263	282	302	322	342	361	381	401

#### 3/4" Box Joints

Board widths are determined by the total number of pins and sockets in the joint design and whether the joint is symmetrical or asymmetrical. Use this chart to determine board widths up to 15<sup>5</sup>/<sub>8</sub>" [397mm].



Symmetrical Joints have a full pin at each board edge. Total no. of pins and sockets is always an odd number.



Asymmetrical joints have a full pin on one edge and a full socket on the other edge. Total no. of pins and sockets is always an even number.

	Syı	mmetric	al Board	Width	Chart for	· 3/4" Bo	x Joints			
Total Pins & Sockets	3	5	7	9	11	13	15	17	19	
Inches	2 11/32"	3 <sup>29</sup> ⁄32"	5 <sup>15</sup> / <sub>32</sub> "	7 ¼32"	8 <sup>19</sup> / <sub>32</sub> "	10 32"	11 <sup>23</sup> / <sub>32</sub> "	13 %32"	14 27/32"	
Millimeters	60	99	139	179	218	258	298	337	377	
	Asy	mmetri	cal Boarc	d Width	Chart fo	r 3/4" B	ox Joints	;		
Total Pins & Sockets		4	6	8	10	12	14	16	18	20
Inches		3 1/8"	4 11/16"	6 1⁄4"	7 <sup>13</sup> ⁄16"	9 <del>3/</del> 8"	10 15/16"	12½"	14 1⁄16"	15 %"

76

#### **Board Width Selection for Box Joints cont.**

#### 3/16" Box Joints

Board widths are determined by the total number of pins and sockets in the joint design and whether the joint is symmetrical or asymmetrical. Use this chart to determine board widths up to 8'' [203mm] for 3/16'' joints. For wider boards, see leighjigs.com.



**Symmetrical Joints** have a full pin at each board edge. The total number of pins and sockets will always be an odd number.



**Asymmetrical Joints** have a full pin at one edge and a full socket at the other. The total number of pins and sockets will always be an even number.

				S	ymm	etric	al Bo	ard	Widt	h Cha	art fo	or 3/1	6" Be	ox Joi	nts					
Total Pins & Sockets	3	5	7	9	11	13	15	17	19	21	23	25	27	29	31	33	35	37	39	41
Inches	%16"	31/32"	1 11/32"	1 3⁄4"	2 1⁄8"	2 17/32"	2 <sup>29</sup> / <sub>32</sub> "	3 5⁄16"	3 11/16"	4 ¾32"	4 15/32"	4 7⁄8"	5 1⁄4"	5 <sup>21</sup> / <sub>32</sub> "	6 1/32"	6 7/16"	6 <sup>13</sup> ⁄16"	7 7⁄32"	7 <sup>19</sup> ⁄32"	8"
Millimeters	14	25	34	44	54	64	74	84	94	104	114	124	133	144	153	164	173	183	193	203
				A	symn	netri	cal Bo	oard	Widt	th Ch	art f	or 3/'	16" B	ox Jo	ints					
Total Pins & Sockets		4	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40
Inches		25/32"	1 5⁄32"	1 %16"	1 <sup>15</sup> ⁄16"	2 11/32"	2 <sup>2</sup> 3⁄32"	3 1/8"	3 ½"	3 <sup>29</sup> / <sub>32</sub> "	4 %32"	4 11⁄16"	5 ¼16"	5 <sup>15</sup> / <sub>32</sub> "	5 <sup>27</sup> / <sub>32</sub> "	6¼"	6 5⁄8"	7 1⁄32"	7 <sup>1</sup> 3⁄32"	7 <sup>1</sup> 3⁄16"
Millimeters		20	29	40	49	60	69	79	89	99	109	119	129	139	148	159	168	179	188	198

### 3/32" Box Joints

Board widths are determined by the total number of pins and sockets in the joint design and whether the joint is symmetrical or asymmetrical. Use this chart to determine board widths up to 4"[102mm] for 3/32" joints. For wider boards, see leighjigs.com.



**Symmetrical Joints** have a full pin at each board edge. The total number of pins and sockets will always be an odd number.



**Asymmetrical Joints** have a full pin at one edge and a full socket at the other. The total number of pins and sockets will always be an even number.

				S	ymm	etric	al Bo	ard V	Vidtł	n Cha	rt fo	or 3/32	2" Bo	x Joi	nts					
Total Pins & Sockets	3	5	7	9	11	13	15	17	19	21	23	25	27	29	31	33	35	37	39	41
Inches	<sup>9</sup> /32"	15/32"	11/16"	7⁄8"	1 ¼16"	1 1⁄4"	1 15/32"	1 21/32"	1 27/32"	2 1/32"	2 1⁄4"	2 7/16"	2 5⁄8"	2 <sup>13</sup> ⁄16"	3 1/32"	3 7/32"	3 13/32"	3 <sup>19</sup> /32"	3 <sup>1</sup> 3⁄16"	4
Millimeters	7	12	17	22	27	32	37	42	47	52	57	62	67	71	77	82	87	91	97	102
				As	symm	etri	cal Bo	oard \	Widt	h Cha	art fo	or 3/3	2" B	ox Joi	ints					
Total Pins & Sockets		4	6	<b>As</b> 8	<b>ymm</b> 10	12	cal Bo	Dard	Widt	h Cha 20	art fo	or 3/3 24	2" Bo	<b>0X JOi</b> 28	i <b>nts</b> 30	32	34	36	38	40
Total Pins & Sockets Inches		4 3⁄8"	6 %16"													32 3 ½8"	34 3 5⁄16"	36 3 ½"	38 3 <sup>11</sup> ⁄16"	40 3 <sup>29</sup> /32"

